



Paint Corner

Direct sales

PRODUCT INFORMATION

PRODUCT NAME:	NEW ETCH PRIMER
DESCRIPTION: PRODUCT BENEFIT :	A fast drying solvent QD Etch Primer. Rapid air-drying. Excellent adhesion to steel. Easy application. Good general durability. Top coats eg. Quick drying and polyurethane enamels are easily accepted, may be overcoated in 3 hrs after flash - off has taken place. Protects steel against corrosion and has excellent promoted adhesion (Zinc phosphate).
PREPARATION:	Surfaces should be properly clean and dry.
TECHNICAL DATA:	<u>Type:</u> Styrenated Alkyd 55% <u>Gloss Level:</u> Matt Finish <u>Re Coating Time:</u> Within 4 - 6 hrs <u>Theoretical Spreading rate:</u> 6 - 8 m ² depending on application. <u>Viscosity:</u> 35 - 45 seconds FC 4 @ 23°C <u>Specific Gravity:</u> 1.150-1.25 <u>Drying Time:</u> Surface: 30 min - 1 hr at 23°C Hard Dry: 1 - 3 hrs at 23°C <u>Shelf Life:</u> 12 months
COLOUR RANGE:	Green, Black, Red, Grey
METHODS OF APPLICATION:	Dipping, brush or spray.
THINNING:	Etch, QD, Lacquer Thinners
CLEAN UP:	Etch, QD, Lacquer Thinners
PRECAUTION:	Flammable. Uses only on clean surfaces that have been prepared correctly (oil free, dust free) Wear safety gear eg. Goggles and gloves. Apply in a ventilated area.
PACKAGING:	1 - 5 - 20 litres
FLASHPOINT:	60 °C

The above information is given without any warranty, as application is out of our control. This data sheet may be changed without notice. The user should contact our Technical Division at our Head Office for any further information.